



Cable ID: PCI6-F/8 1-1

Test Summary: PASS



Date / Time: 03/21/2019 05:48:17pm
Headroom: 2.1 dB (NEXT 36-45)
Test Limit: ISO Patch Cord Cat6A 2.5m
 Cable Type: Cat 6A F/UTP

Operator: MGA
 Software Version: 2.7800
 Limits Version: 1.9500
 NVP: 74.0%

Model: DTX-1800
 Main S/N: 8788118
 Remote S/N: 8788119
 Main Adapter: DTX-PC6A/MN ANSI/TIA
 Remote Adapter: DTX-PC6A/SR ANSI/TIA

Wire Map (T568B)


PASS



Length (ft)	[Pair 78]	7
Prop. Delay (ns)	[Pair 12]	11
Delay Skew (ns)	[Pair 12]	1
Resistance (ohms)	[Pair 45]	0.7

Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	2.1		2.1	
Freq. (MHz)	486.0		486.0	
Limit (dB)	31.4		31.4	



PASS	MAIN	SR	MAIN	SR
Worst Pair	36		36	
RL (dB)	4.3		4.3	
Freq. (MHz)	435.0		435.0	
Limit (dB)	10.4		10.4	

