



Cable ID: DIRECTPATCH-7,9M--UTP

Date / Time: 03/25/2019 10:53:20 AM

Headroom 1.3 dB (NEXT 36-45)

Test Limit: ISO Patch Cord Cat6A 7.5m

Cable Type: Cat 6A U/UTP

NVP: 68.2%

Operator: MGA

Software Version: 2.7800

Limits Version: 1.9500

Calibration Date:

Main (Tester): 08/16/2017

Remote (Tester): 08/16/2017

Test Summary: PASS

Model: DTX-1800


Main S/N: 8788118

Remote S/N: 8788119


Main Adapter: DTX-PC6A/MN ISO/IEC

Remote Adapter: DTX-PC6A/SR ISO/IEC

Length (ft)	[Pair 12]	26
Prop. Delay (ns)	[Pair 36]	41
Delay Skew (ns)	[Pair 36]	2
Resistance (ohms)	[Pair 45]	1.4



Wire Map (T568B)
PASS



Worst Case Margin Worst Case Value

PASS	MAIN	SR	MAIN	SR
Worst Pair	36-45		36-45	
NEXT (dB)	1.3		1.3	
Freq. (MHz)	480.0		480.0	
Limit (dB)	31.9		31.9	

PASS	MAIN	SR	MAIN	SR
Worst Pair	12		12	
RL (dB)	4.1		4.1	
Freq. (MHz)	312.0		312.0	
Limit (dB)	12.6		12.6	

